

True All-in-One Compact POS Terminal SGT-116A with 3" Thermal Printer

11.6" Capacitive Touch Screen Android POS Terminal



I/O Ports & RJ11/12 Drawer Port



with 4.3" TFT LCD Second Display



with 2 x 20 character VFD display

SGT-116A Specification

OS	Android 11.0
CPU & RAM	ARM RK3568 2.0GHz DDR4 2GB (4GB, 8GB Option)
Storage	eMMC 16GB as standard
Printer	80mm SEIKO Head Thermal Printer (60mm diameter) * Speed: 160 mm/sec with Auto Cutter 58mm width Roll Paper is also available using separator plate Multinational character set, Reliability printing: 100KM, Cutter life: 1 million times
Main Display	11.6" TFT LCD Screen (WXGA resolution 1366 x 768 pixel) with Capacitive Touch Panel, Brightness: 250cd
Customer Display	4.3" LCD Second Display(800 x 480), VFD 2 x 20 character (Option)
In/Out Ports	DC-input x 1, HDMI x 1, LAN RJ45 100M x 1, SIM x 1, Audio x 1, USB3.0 x 2, USB2.0 x 2, TF Card x 1, RJ11 x 1, Bluetooth & Wi-Fi on board as standard
Environment	Operating temperature and humidity : -20°C - 50°C Storage temperature and humidity : -30°C - 70°C
Power Supply	Input: AC100-240V/2.5A Output: DC12V-5A
Dimension/Weight	288(W) x 298 (D) x 97(H) mm / Net Weight: 2.75kg
Option	4.3" Customer Display, VFD Display, 2D Barcode Scanner, NFC Reader, Battery Operation is available (6 pcs rechargeable battery 6000mAh Output: DC16V-5A)