

**- TP Series True All in One Compact POS Terminal -**

# TCS TPA-116a

**11.6" Capacitive Touch Screen For Retail and Hospitality**



## TCS TPA-116a Specification

OS	Android 11.0
CPU & RAM	Rock chip RK3568 Quad-Core Cortex-A55 DDR3/DDR4 2GB
Storage	16GB eMMC as standard
Printer	80mm Icod Head or SEIKO Head Thermal Printer * Speed: 200 mm/sec with Auto Cutter Multinational character set, Reliability printing: 100KM, Cutter life: 1 million times or 58mm Thermal Printer * Speed: 90 mm/sec without Auto Cutter
Main Display	11.6" Touch TFT Screen (WXGA resolution 1366 x 768 pixel) with Capacitive Touch Panel
Customer Display (Option)	5" LCD Second Display without RFID, Barcode Scanner or VFD 2 x 20 character, VFD 2 x 20 character
In/Out Ports	USB2.0 x 5, COM x 2, LAN 10/100mbps Ethernet RJ45, RJ11/12, Audio out/input, TF card, Bluetooth 4.0, Wi-Fi IEEE 802.11b/g as standard
Environment	Operating temperature and humidity : -10°C - 40°C, 20 - 80% Storage temperature and humidity : -20°C - 50°C, 20 - 90%
Power Supply	Input: AC100-240V/1.5A Output: DC12V 5A
Dimension/Weight	300 (W) x 316 (D) x 102(H) mm / Net Weight: 3.5kg
Option	RFID, 2D Barcode Scanner, MSR, 4G LTE, Battery Operation (6400mAh)