

Touch POS Terminal TP-150

15" Solid Aluminum Housing
Capacitive Touch TFT LCD POS True Flat Screen
Powerful Performance Intel Celeron J1900 or J4125



Second Display (Option)



Solid Aluminum Housing

TP-150 Specifications

Screen	15" (4:3) Touch TFT LCD (1024 x 768 Resolution) with Capacitive Touch
CPU	Intel Celeron J1900 2.00 - 2.42GHz Cache 2MB or J4125 2.00 - 2.70GHz, Cache 4MB
Memory	DDR3: 4GB for J1900, DDR4: 4GB for J4125, Storage: SSD64GB as standard
OS / Power Supply	Win 8/10, Linux / Power supply: AC 100-240V/3.5A, Output DC12V 5A
In/Out Ports	USB2.0 4 port, USB3.0 2 port, COM 2, RJ-45 LAN 10/100/1000 Mbps for J1900, 10/100 Mbps for J4125, Audio: x 1, VGA DB-15 x 1, DC Jack 12V, RJ11/12 Drawer Jack
Environment	Operating Temperature: 0°C - 40°C, Storage temperature: -40°C - 50°C
Dimension/Weight	356 (W) x 346 (H) x 222 (D) mm Net Weight: 4.3 Kg
Option	Customer Display (2 x 20 VFD or 2 x 20 LCD) Second Display LCD (without Touch) 10.1" CPU: Intel CORE i3, i5 Memory : DDR3/DDR4: UP to 8GB / SSD 128GB, 256GB MSR with I-Button Dallas key combo, RFID, Wi-Fi, Wall Mounting